



**MOTOREX**<sup>®</sup>  
Oil of Switzerland

***DRIVEN BY HIGH PERFORMANCE***

**PROUDLY DISTRIBUTED BY**

**AUTOMATIC  
DISTRIBUTORS**

## 2-STROKE OILS

### FORMULA 2T

- Synthetic blend.
- Suitability for use with catalytic converters checked.
- Minimal combustion residues.
- Especially low smoke.
- For pre-mix and separate lubrication.

Size	QTY/CS	MFG #	Part #
1-L	10	308244	746180



### POWER SYNT 2T

- Fully synthetic high-performance engine oil for 2-stroke supersport motorcycles.
- This lubricant offers optimum performance and maximum protection as well as extremely clean combustion.
- JASO FD, API TC, ISO-L-EGD

Size	QTY/CS	MFG #	Part #
1-L	10	308248	746216



### CROSS POWER 2T

- Fully synthetic.
- Especially formulated for Off-Road use.
- Racing quality.
- Reduces combustion residues.
- Low-smoke formula, for pre-mix and separate lubrication.
- JASO FD, API TC, ISO-L-EGD.

Size	QTY/CS	MFG #	Part #
1-L	10	308092	746164
4-L	4	303359	746167
20-L	1	309642	746165
60-L	1	303385	746166



### SCOOTER FORZA 2T

- Fully Synthetic
- Reduces combustion residues.
- Optimum cold starting characteristics.
- Ideal for stop-and-go traffic.
- Catalytic converter tested.
- JASO FD, API TC, ISO-L-EGD

Size	QTY/CS	MFG #	Part #
1-L	10	308266	746269



### SCOOTER 2T

- Synthetic-blend.
- Low-smoke formula.
- Reduces combustion residues.
- Optimum cold starting characteristics.
- Ideal for stop-and-go traffic.
- Catalytic converter tested.
- API TC, ISO-L-EGC, JASO FD

Size	QTY/CS	MFG #	Part #
1-L	10	308263	746265



### OCEAN FS 2T BIO

- Quickly biodegradable, fully synthetic two-stroke motor oil.
- Specially developed for petrol engines in the marine sector.
- The high-performance additives combined with synthetic base oils guarantee perfect lubrication – even under difficult operating conditions.

Size	QTY/CS	MFG #	Part #
1-L	12	301530	746212



## 4-STROKE OILS

### TOP SPEED 4T SAE 5W/40 MA2

- Synthetic performance.
- Excellent wear protection.
- Particularly good thermal and shear stability.
- Reduces oil consumption.
- Catalytic converter tested.

Size	QTY/CS	MFG #	Part #
1-L	10	308272	746283
20-L	1	305595	746284



### TOP SPEED 4T SAE 10W/30 MA2

- Synthetic performance.
- Excellent wear protection.
- Particularly good thermal and shear stability.
- Reduces oil consumption.
- JASO MA2; API SL, SM, SN

Size	QTY/CS	MFG #	Part #
1-L	10	308270	746273
20-L	1	305591	746274



**4-STROKE OILS CONTINUED**

**TOP SPEED 4T SAE 10W/40 MA2**

- Top Speed 10W40 is a fully synthetic engine oil is designed for use in 4-stroke motorcycle engines.
- JASO MA2; API SL, SM, SN

Size	QTY/CS	MFG #	Part #
1-L	10	308271	746277
4-L	4	304973	746276
20-L	1	305592	746281
200-L	1	304961	746275



**TOP SPEED 4T SAE 15W/50 MA2**

- Synthetic performance.
- Excellent wear protection.
- Particularly good thermal and shear stability.
- Reduces oil consumption
- JASO MA2; API SL, SM, SN.

Size	QTY/CS	MFG #	Part #
1-L	10	308096	746280
4-L	4	304975	746279
20-L	1	305594	746282
200-L	1	304980	746278



**POWER SYNT 4T SAE 5W/40**

- Fully synthetic.
- Serious power delivery.
- Racing quality.
- Optimum wear protection.
- Extremely good thermal and shear stability.
- Catalytic converter tested.
- Ideal for wet multi-disc clutches.

Size	QTY/CS	MFG #	Part #
1-L	10	308093	746227
4-L	4	305658	746223
20-L	1	305655	746228
200-L	1	305652	746226



**POWER SYNT 4T SAE 10W/50**

- Fully synthetic high-performance 4-stroke engine oil, specially developed for demanding use in hyper-sport motorcycles with powerful engines.
- These lubrications provide engines, gearboxes and clutches with optimum protection over the entire range of applications.
- JASO MA2 approval guarantees the fault-free functioning of wet multi-disc clutches.

Size	QTY/CS	MFG #	Part #
1-L	10	308249	746219
4-L	4	305664	746218
20-L	1	305661	746224
200-L	1	305660	746217



**POWER SYNT 4T SAE 10W/60**

- Fully synthetic high-performance 4-stroke engine oil, specially developed for demanding use in hyper sport motorcycles with powerful engines.
- These lubrications provide engines, gearboxes and clutches with optimum protection over the entire range of applications.
- JASO MA2; API SL, SM, SN

Size	QTY/CS	MFG #	Part #
1-L	10	308252	746220
4-L	4	306210	746222
20-L	1	306209	746225
200-L	1	306207	746221



**CROSS POWER 4T SAE 5W/40**

- Fully synthetic.
- Especially formulated for the toughest Off-Road use.
- Racing quality.
- Extremely high thermal and shear stability.
- Catalytic converter tested.

Size	QTY/CS	MFG #	Part #
1-L	10	308243	746175
4-L	4	305678	746177
20-L	1	305677	746176



**CROSS POWER 4T SAE 10W/60**

- Fully synthetic.
- Especially formulated for the toughest Off-Road use.
- Racing quality.
- Extremely high thermal and shear stability.
- Catalytic converter tested.
- JASO MA2; API SL, SM, SN

Size	QTY/CS	MFG #	Part #
1-L	10	308242	746172
4-L	4	306217	746173
20-L	1	306216	746174



**CROSS POWER 4T SAE 10W/50**

- Fully synthetic.
- Especially formulated for the toughest Off-Road use.
- Racing quality.
- Extremely high thermal and shear stability.
- Catalytic converter tested.
- JASO MA2; API SL, SM, SN.

Size	QTY/CS	MFG #	Part #
1-L	10	308241	746171
4-L	4	305692	746169
20-L	1	305687	746170
200-L	1	305685	746168



**4-STROKE OILS CONTINUED**

**BOXER 4T SAE 5W40**

- Synthetic high-performance engine oil, specifically for use in water-cooled boxer engines.
- Guarantees a stable lubricating film and a constantly high oil pressure under all operating conditions and lowers the friction in the engine significantly.
- JASO MA2; API SL, SM, SN

Size	QTY/CS	MFG #	Part #
1-L	10	308239	746143
4-L	4	304678	746145
20-L	1	305605	746144



**BOXER 4T SAE 15W/50**

- Synthetic high-performance engine oil, specifically for use in 4-stroke boxer engines.
- Guarantees a stable lubricating film and a constantly high oil pressure under all operating conditions and lowers the friction in the engine significantly.
- JASO MA2; API SL, SM, SN

Size	QTY/CS	MFG #	Part #
1-L	10	308240	746140
4-L	4	300273	746141
20-L	1	305606	746142



**RACING PRO 4T SAE 0W/40**

- Fully synthetic.
- Developed and used by MOTOREX Racing Support.
- Tested and proven under the most extreme racing conditions.
- Exceptionally high shear strength and friction reduction.
- Optimal wear protection.

Size	QTY/CS	MFG #	Part #
1-L	10	308255	746256
4-L	4	303105	746257



**RACING PRO 4T SAE 15W/50**

- Fully synthetic
- Tested and proven under the most extreme racing conditions
- Exceptionally high shear strength and friction reduction
- Optimal wear protection
- Withstands the highest loads during races

Size	QTY/CS	MFG #	Part #
1-L	10	308256	746258
4-L	4	303106	746259



**FORMULA 4T SAE 10W/40**

- High-quality synthetic blend motor oil for four-stroke motorbikes.
- This oil offers a very good level of protection for engines, gears and clutches in all fields.
- JASO MA2; API SL, SJ, SH, SG

Size	QTY/CS	MFG #	Part #
1-L	10	308273	746181
4-L	4	306189	746183
20-L	1	306184	746186
200-L	1	306186	746182



**FORMULA 4T SAE 15W/50**

- High-quality synthetic blend motor oil for four-stroke motorbikes.
- This oil offers a very good level of protection for engines, gears and clutches in all fields.
- JASO MA2; API SL, SJ, SH, SG

Size	QTY/CS	MFG #	Part #
1-L	10	308274	746184
4-L	4	306183	746185
20-L	1	306174	746188
200-L	1	306176	746187



**ATV QUAD 4T SAE 10W/40 MA2**

- Offers a good level of shear stability and a short lubrication rise time, even at low temperatures.
- Formulated for tough conditions in the four-stroke engines of ATVs.

Size	QTY/CS	MFG #	Part #
1-L	10	308237	746139



## 4-STROKE OILS CONTINUED

### SCOOTER 4T SAE 10W/30 MB

- Optimal cold-starting properties.
- Very good wear protection.
- Ideal for stop-and-go traffic.

Size	QTY/CS	MFG #	Part #
20-L	1	306260	746266



### SCOOTER 4T SAE 10W/40 MA2

- Optimal cold-starting properties.
- Very good wear protection.
- Ideal for stop-and-go traffic.
- JASO MA2; API SL, SJ, SH, SG

Size	QTY/CS	MFG #	Part #
1-L	10	308264	746268
20-L	1	306256	746267



## TRANSMISSION & GEAR OILS

### SCOOTER GEAR OIL ZX SAE 80W/90

- Superior load-carrying capacity.
- Highly comfortable shifting across the entire temperature range.
- Excellent wear protection.
- Good viscosity-temperature behavior.
- Excellent oxidation stability and resistance to aging.
- JASO MA2; API SL, SM, SN

Size	QTY/CS	MFG #	Part #
130-ML	12	301158	746270



### ATF DEXRON III

- Designed for KTM 50cc motorcycles 2008 and newer
- High thermal and shear stability
- Smooth clutch engagement
- Steady, controllable power

Size	QTY/CS	MFG #	Part #
1-L	10	308063	746137



### TRIAL GEAR OIL 75W

- Trial Gear Oil 75W is a fully synthetic transmission oil designed for the specific clutch engagement requirements of trial motorcycles.
- Highly effective additive composition for optimal clutch feel and engagement.
- Smooth and consistent clutch modulation under constant, extreme loads.
- Recommended for and developed with Gas Gas trials.

Size	QTY/CS	MFG #	Part #
1-L	10	308875	746286
20-L	1	309799	746285



### GEAR OIL HYPOID SAE 80W/90

- Gear Oil Hypoid 80W90 is a API GL-5 Gear Oil is designed to increase resistance to breakdown under high temperature and the mechanical pressure produced by hypoid gear boxes and universal joints.
- API GL-5

Size	QTY/CS	MFG #	Part #
1-L	10	308064	746190



### MOTO GEAR OIL SAE 10W/30

- Gear Oil 10W30 is a synthetic oil developed for separately lubricated gearboxes with wet-clutch.
- SAE 10W/30 (SAE 80W/85) API GL-4

Size	QTY/CS	MFG #	Part #
1-L	10	308066	746189



### PRISMA ZX SAE 75W/90

- Guarantees optimum lubrication over a large temperature range, even under extreme conditions, both in synchronised and unsynchronised manual gearboxes in axles.
- Guarantees reliable lubrication in axle drives and end drives subject to high loads, while at the same time offering flawless functioning of manual gearbox synchronisation.
- API GL-4, GL-5

Size	QTY/CS	MFG #	Part #
1-L	10	308065	746229



## TRANSMISSION & GEAR OILS CONTINUED

### ATF SUPER

- Synthetic automatic transmission fluid designed for ATF Dexron II applications.
- Designed for KTM 50cc motorcycles 2007 and older
- High thermal and shear stability
- Smooth clutch engagement

Size	QTY/CS	MFG #	Part #
1-L	12	300146	746138



### RACING GEAR OIL SAE 10W/40

- Synthetic (Synthetic Performance) with MC technology.
- Developed and used by MOTOREX Racing Support.
- Tested under the most extreme racing conditions.
- Optimal wear protection.
- Withstands maximum loads during races.

Size	QTY/CS	MFG #	Part #
1-L	12	303086	746253



## CLEAN & CARE

### MOTO CLEAN UNIVERSAL

- More intensive cleaning effect, better penetration and optimised adhesion.
- Very good compatibility with rubber, plastics and metal.
- Spray head with three functions: direct jet, fine spray and "STOP" for closed nozzle.
- Ready to use but can also be diluted.
- Pump spray bottle can be reused multiple times with the 5-litre refill.

Size	QTY/CS	MFG #	Part #
1-L	12	307834	746204
5-L	4	309399	746206
20-L	1	310011	746205



### MOTO CLEAN PLUS

- Lower pH value formula, has a better distribution over surfaces.
- Excellent compatibility with rubber, plastics and metal.
- Can be used overhead thanks to the MOTOREX 360° technology and special spray head.
- Ready to use but can also be used diluted to a ratio of 1:3 for cleaning small amounts of dirt.
- Pump spray bottle can be reused multiple times with the 5-litre refill.

Size	QTY/CS	MFG #	Part #
1-L	6	304371	746202
5-L	4	304372	746203
20-L	1	309685	746201



### MOTO QUICK CLEANER

- Beading effect.
- 360-degree spraying system (500 ml).
- Cleans plastics, visors, windscreens and varnished surfaces.
- Removes insects, dirt, dust etc.
- Particularly stubborn contamination is easily removed.
- Quick and easy cleaning – perfect for on the road too.
- Does not require additional water.

Size	QTY/CS	MFG #	Part #
60-ML	12	304994	746210
500-ML	12	304379	746208
5-L	4	304458	746209



## FORK & SHOCK OILS

### RACING FORK OIL 2.5W

- Improved breakaway torque (stick-slip).
- Fork oil specially developed for modern fork systems.
- Significantly improved thermal stability.
- Adaptation of the viscosity index in the maximum range.
- Improved shear stability.
- Optimum air release.

Size	QTY/CS	MFG #	Part #
1-L	6	306402	746241
20-L	1	309719	746242
60-L	1	305415	746243



### RACING FORK OIL 4W

- Improved breakaway torque (stick-slip).
- Fork oil specially developed for modern fork systems.
- Significantly improved thermal stability.
- Adaptation of the viscosity index in the maximum range.
- Improved shear stability.
- Optimum air release.

Size	QTY/CS	MFG #	Part #
1-L	6	306404	746250
20-L	1	309714	746251
60-L	1	305365	746252



**FORK & SHOCK OILS CONTINUED**

**RACING FORK OIL 5W**

- Improved breakaway torque (stick-slip).
- Fork oil specially developed for modern fork systems.
- Significantly improved thermal stability.
- Adaptation of the viscosity index in the maximum range.
- Improved shear stability.
- Optimum air release.

Size	QTY/CS	MFG #	Part #
1-L	6	306406	746244
20-L	1	309720	746245
60-L	1	305424	746246



**RACING FORK OIL 7.5W**

- Improved breakaway torque (stick-slip).
- Fork oil specially developed for modern fork systems.
- Significantly improved thermal stability.
- Adaptation of the viscosity index in the maximum range.
- Improved shear stability.
- Optimum air release.

Size	QTY/CS	MFG #	Part #
1-L	6	306408	746247
20-L	1	309721	746248
60-L	1	305456	746249



**RACING FORK OIL 10W**

- Improved breakaway torque (stick-slip).
- Fork oil specially developed for modern fork systems.
- Significantly improved thermal stability.
- Adaptation of the viscosity index in the maximum range.
- Improved shear stability.
- Optimum air release.

Size	QTY/CS	MFG #	Part #
1-L	6	306410	746235
20-L	1	309724	746236
60-L	1	305492	746237



**RACING FORK OIL 15W**

- Improved breakaway torque (stick-slip).
- Fork oil specially developed for modern fork systems.
- Significantly improved thermal stability.
- Adaptation of the viscosity index in the maximum range.
- Improved shear stability.
- Optimum air release.

Size	QTY/CS	MFG #	Part #
1-L	6	306412	746238
20-L	1	309723	746239
60-L	1	305478	746240



**RACING SHOCK OIL**

- Formulated with 3D response technology for optimal low friction damping at all temperatures.
- Designed for use in modern fork systems and available in various weights for all applications.
- Fade-free formula withstands high thermal loads
- Low friction performance

Size	QTY/CS	MFG #	Part #
1-L	6	307516	746261
20-L	1	309769	746262
60-L	1	307513	746264



**RACING SHOCK OIL SD-1**

- Shock oil that has superb damping performance.
- Optimum corrosion protection.
- Excellent air separation abilities.
- Outstanding protection against aging.
- Reliable wear protection.

Size	QTY/CS	MFG #	Part #
5-L	4	301994	746260



**MAINTENANCE**

**COPPER PASTE**

- Application range -40 °C / +1200 °C.
- Protection against metal contacts, prevents nuts from jamming and resistant to frictional corrosion.
- Good high-pressure properties.
- Contains no graphite, molybdenum disulfide and no lead.

Size	QTY/CS	MFG #	Part #
100-G	18	301806	746161
850-G	12	301805	746162



**WHITE GREASE**

- Lithium-based white lubricant grease especially for bicycles.
- MOTOREX WHITE GREASE has outstanding wear-reducing properties and remains malleable at cold temperatures.
- Ideal for slide bearings and crank sets.

Size	QTY/CS	MFG #	Part #
850-G	12	300775	746288



**MAINTENANCE CONTINUED**

**FETT (GREASE) 2000**

- Incredibly adhesive calcium soap grease with a high level of oxidation resistance.
- Features excellent resistance to water and outstanding pressure-bearing capacity.

Size	QTY/CS	MFG #	Part #
400-G	10	300787	746192
850-G	12	300746	746191



**FETT (GREASE) 3000**

- High-performance lithium complex grease based on a high-quality mineral oil. Suitable for challenging lubrication points.
- Specially designed for use in heavily loaded roller bearings.
- However, this high-pressure grease can also be used in smaller, fast-turning ball bearings and needle bearings.

Size	QTY/CS	MFG #	Part #
850-G	12	300766	746193



**ANTI SEIZE**

- Special mounting paste for metal and aluminum connections including any parts that need to be press-fit, aluminum supports in metal frames and all screw connections.

Size	QTY/CS	MFG #	Part #
100-G	12	309922	746134
850-G	12	309921	746135



**ETHANOL TREATMENT**

- Properties reduce phase separation/separation, optimize fuel efficiency and reduce corrosion.
- Ensures that the engine runs more easily, removes deposits in the combustion chamber, regenerates old fuel and helps to remove water from the system.

Size	QTY/CS	MFG #	Part #
250-ML	12	305642	746179



**HYDRAULIC FLUID 75**

- High seal compatibility.
- Outstanding resistance to ageing.
- Not hygroscopic.
- More reliable, fast response behaviour.
- High viscosity index.
- Outstanding operating temperature range.

Size	QTY/CS	MFG #	Part #
250-ML	12	308841	746198
1-L	12	300230	746197



**TYRE MOUNTING FLUID**

- Special, fast-drying and economical tyre mounting fluid for effortless mounting and removal of all conventional tyres.
- Tested for tyre pressure monitoring systems. (TPMS).
- Does not leave any visible residues after mounting.

Size	QTY/CS	MFG #	Part #
100-ML	12	305514	746287



**COOLANT M3.0 READY TO USE**

- Silicate-, nitrite-, amine- borate- and phosphate-free.
- Free from 2-ethylhexanoic acid.
- Extremely effective corrosion protection for the entire cooling system.
- Excellent compatibility with all commercially available seals and cooler hoses.
- Excellent thermal conductivity.
- Extended usage duration.

Size	QTY/CS	MFG #	Part #
1-L	10	308100	746157
20-L	1	309680	746158



**COOLANT M5.0 READY TO USE**

- Nitrite-, amine- and borate-free.
- Does not contain 2-Ethylhexanoic acid.
- Good corrosion protection for metals and alloys in the cooling system.
- Good compatibility with commercially available elastomer and plastics high chemical stability.
- Recommended usage duration 3 years.

Size	QTY/CS	MFG #	Part #
1-L	10	308275	746160
20-L	1	309672	746159



**MAINTENANCE CONTINUED**

**AIR FILTER OIL 206**

- Specially developed air filter oil for foam air filter elements with good adhesion.
- Keeps out sand, dust and water.
- Guaranteed optimal air flow.
- Very good adhesion.

Size	QTY/CS	MFG #	Part #
1-L	12	300052	746132



**AIR FILTER CLEANER**

- Cleaning agent for foam filter elements.
- Free of solvents, biodegradable and non-combustible.

Size	QTY/CS	MFG #	Part #
1-L	12	300044	746131
4-L	4	300043	746130



**RACING BIO AIR FILTER OIL**

- Air filter oil specially developed for off-road motorbikes and quads (ATVs) that feature a reusable foam air filter.
- This biodegradable special oil has excellent absorption capacity with regards to dust and dirt.
- Thanks to the special substances it contains, harmful foreign bodies are prevented from entering the engine – even in the toughest usage conditions.

Size	QTY/CS	MFG #	Part #
1-L	12	303816	746233



**RACING BIO AIR FILTER CLEANER**

- A cleaner in powder form specially developed for off-road motorbikes and quads (ATVs) that feature a reusable foam air filter.
- Thanks to its active substances, it also quickly dissolves the most stubborn dirt.

Size	QTY/CS	MFG #	Part #
900-ML	12	305062	746232



**BRAKE FLUID DOT 4**

- High-performance, premium brake fluid of outstanding quality, with a high wet boiling point and thus extreme safety reserve against vapor lock.

Size	QTY/CS	MFG #	Part #
250-ML	12	300280	746147
1-L	12	300296	746146



**BRAKE FLUID DOT 5.1**

- For hydraulic brake and clutch systems with a boiling point of at least 260 °C and an extremely high wet boiling point of at least 180 °C. Because of the low viscosity at low temperatures, particularly suitable for additional systems, such as ABS and ASR.

Size	QTY/CS	MFG #	Part #
250-ML	12	300287	746149
1-L	12	303261	746148



**RACING BRAKE FLUID**

- Exceptionally high wet boiling point.
- Tested and proven under the most extreme racing conditions.
- Can be used in all ABS and ADS systems without any problems.

Size	QTY/CS	MFG #	Part #
500-ML	12	303274	746234



**SPRAYS AND AEROSOLS**

**JOKER 440 SYNTHETIC SPRAY**

- Fully synthetic, universal lubricating and corrosion protection spray.
- Leaves behind a highly effective protective film.
- Creeps under water, protects against corrosion, takes effect electrically and cleans and maintains metals and plastics.

Size	QTY/CS	MFG #	Part #
500-ML	12	302317	746200



**OIL SPRAY BIO**

- Biodegradable oil spray for industry, the trade sector, household and hobbies.
- Lubricates all moving parts, protections against corrosion and leaves behind a colourless, thin, protective film.

Size	QTY/CS	MFG #	Part #
500-ML	12	302323	746213



**ANTIRUST SPRAY**

- Rust remover and screw releaser with outstanding creep effect.
- Quickly loosens seized-up metal parts.
- Protects against corrosion and repels moisture.
- Rust-loosening, water-repellent and lubricating.

Size	QTY/CS	MFG #	Part #
500-ML	12	302338	746136



**POWER BRAKE CLEAN SPRAY**

- Brake cleaner decreases and cleans all brake and coupling parts under high pressure without leaving any residue.
- Reliably dissolves and removes oil, grease, tar, brake fluid, dirt, etc.
- Does not attack rubber, plastic or paint.

Size	QTY/CS	MFG #	Part #
750-ML	12	302291	746214



**MOTO PROTECT SPRAY**

- Repels moisture and the fine oil film protects the treated surfaces against corrosion.
- It is also easy to apply, since the 0.5-litre spray can also be used upside down.

Size	QTY/CS	MFG #	Part #
500-ML	12	304250	746207



**MOTO SHINE MS 1**

- Special gloss spray for the perfect finish after cleaning a vehicle.
- Gives a lasting shine to varnish, plastic, chrome, etc. and forms an anti static film with drop-repellent effect.

Size	QTY/CS	MFG #	Part #
500-ML	12	309451	746211



**POWER CLEAN SPRAY**

- Cleans and degreases even in the event of stubborn dirt.
- Reliably dissolves oil, grease, tar etc. without leaving behind any residues.
- Cleans ignition plugs, battery terminal posts, electrical connections and contacts.
- Safe for rubber, plastic and varnish.

Size	QTY/CS	MFG #	Part #
500-ML	12	302327	746215



**SPRAY WITH PTFE**

- A dry-film lubricant; it can be used as an anti-friction agent and separating agent that does not leave behind any oily marks.
- With a particle size of 5 µm, the wafer-thin PTFE layer prevents parts from sticking together in designs or systems with machine tools.
- Almost absolute chemical resistance and a very broad service temperature range (+265°C). Anti-static.

Size	QTY/CS	MFG #	Part #
500-ML	12	302349	746231



**SPRAYS AND AEROSOLS CONTINUED**

**CHAINLUBE OFF ROAD**

• Chain Lube Off-Road is a full synthetic, water-repellent, clear chain lubricant specifically engineered for off-road motorcycles.

Size	QTY/CS	MFG #	Part #
500-ML	12	302281	746154



**CHAINLUBE RACING SPRAY**

• Chain Lube Racing is a light-weight water resistant, white chain lubricant specifically road racing applications.

Size	QTY/CS	MFG #	Part #
500-ML	12	302336	746155



**CHAINLUBE ROAD STRONG**

• Chain Lube Road Strong is a thick, water resistant, white chain lubricant specifically engineered for road riding applications.

Size	QTY/CS	MFG #	Part #
500-ML	12	302347	746156



**CHAINLUBE ADVENTURE**

• Water-resistant, extremely adhesive lubricating film.  
• O-ring and X-ring tested.  
• Low dirt adhesion.  
• High-pressure and sling-off resistant.  
• Reduces wear and tear.

Size	QTY/CS	MFG #	Part #
200-ML	12	307861	746153
500-ML	12	306442	746152



**AIR FILTER OIL SPRAY 655**

• Specially developed air filter oil spray for foam air filter elements.  
• Keeps out sand, dust and water.  
• Guaranteed optimal airflow.  
• Very good adhesion.

Size	QTY/CS	MFG #	Part #
750-ML	12	303080	746133



**ACCU PROTECT SPRAY 200 ML**

• Protects battery terminal posts, pole terminals, connectors and starter connection cables.  
• Prevents corrosion and oxidation.

Size	QTY/CS	MFG #	Part #
200-ML	12	302288	746129



**CARBURETOR SPRAY**

• Cleans air passages, inlet flaps, Venturi tubes, adjustment screw seats and carburetor housings.  
• Suitable for all types of carburetor.  
• Tested and found suitable for use in carburetor.

Size	QTY/CS	MFG #	Part #
500-ML	12	302293	746150



**PROTEX SPRAY**

• Textile and leather impregnation.  
• Highly effective, long-lasting protection against wet conditions and oil.  
• Suitable for leather, textiles and microfibers, preserves the natural breath ability of the fabric.

Size	QTY/CS	MFG #	Part #
500-ML	12	302329	746230



**SPRAYS AND AEROSOLS CONTINUED**

**EASY CUT SPRAY**

- Spray for all high-alloyed steel grades as well as non-ferrous metals and aluminum. Increases the machining speed, reduces wear and extends the service life of tools.
- Optimum cooling and lubricating properties.

Size	QTY/CS	MFG #	Part #
250-ML	12	303792	746178



**GUN CARE SPRAY**

- Tested and found suitable for use in O-ring and X-ring chains.
- Cleans, lubricates and preserves all metal parts on an ongoing basis.
- Dissolves powder residues and protects against rust.
- Repels moisture and prevents corrosion caused by hand perspiration.

Size	QTY/CS	MFG #	Part #
300-ML	12	302301	746195



**COPPER SPRAY**

- Preventing the fusing/sticking of parts subject to high thermal stress such as exhaust screws, ignition plugs, brake pads and heat exchangers.
- Noise-absorbing, oxidation-stable, protects against corrosion, very adhesive, salt-water-resistant and extremely temperature-stable.
- Application range: -40 °C to +1200 °C.

Size	QTY/CS	MFG #	Part #
300-ML	12	308778	746163



**SILICONE SPRAY**

- Lubricant, maintenance product and protecting agent for rubber, plastic and all metal parts
- Temperature-stable from -50 degree C to +200 degree C
- Water-repelling
- Prevents oxidation
- Anti-static

Size	QTY/CS	MFG #	Part #
500-ML	12	303082	746271



**SPRAY 2000**

- Long-acting, fully-synthetic, high-pressure-resistant lubricant for universal application.
- Penetrates rapidly and protects from corrosion.
- Thermally stable against -30 °C to +200 °C.
- Adhesive, water resistant, silicone free, pressure and impact resistant, colorless.

Size	QTY/CS	MFG #	Part #
500-ML	12	302272	746272



**HELMET CARE SPRAY**

- Cleaning and care foam for helmet shell and inner padding.
- Effective and fast.
- Deodorizes and refreshes colors.
- Protects the surfaces.

Size	QTY/CS	MFG #	Part #
200-ML	12	303204	746196



**GREASE SPRAY**

- Viscous grease spray with a good level of adhesive power; can be used as an alternative to a grease brush.
- Water and salt-water-resistant. Excellent corrosion and wear protection.

Size	QTY/CS	MFG #	Part #
500-ML	12	302297	746194



**INTACT MX 50 SPRAY**

- Universal lubricating and corrosion protection spray.
- Leaves behind a highly effective protective film.
- Repels and undermines water, has outstanding creep properties and prevents corrosion.

Size	QTY/CS	MFG #	Part #
500-ML	12	302312	746199



**CHAIN CLEAN DEGREASER**

- Effectively removes caked on residue
- Tested with X-rings and O-rings

Size	QTY/CS	MFG #	Part #
500-ML	12	303087	746151





**MOTOREX**<sup>®</sup>  
Oil of Switzerland

PROUDLY DISTRIBUTED BY

**AUTOMATIC**  
**DISTRIBUTORS**

22 TARGET CIRCLE  
BANGOR, MAINE 04401

207.942.6769  
CUSTSERV@AUTODIST.COM

AUTODIST.COM